

# 972 XE

WHEEL LOADER



---

**Engine Maximum Power**  
**Operating Weight**

253 kW (339 hp)  
24 890 kg (54,858 lb)

Meets U.S. EPA Tier 4 Final and EU Stage V emission standards.



# CAT® 972 XE

## SUPERIOR EFFICIENCY.

The Cat® 972 XE Wheel Loader delivers increased fuel efficiency, premium performance with simple-to-use standard technologies to boost operator efficiencies, and lower maintenance costs. This machine is designed to meet emission standards without interrupting operation. Improved performance, reliability, durability, and versatility result in a machine that is better built to meet your needs.



### WHEEL LOADERS MADE FOR MORE

Cat wheel loaders were built with efficiency in mind, offering you the best in:

- + RELIABILITY
- + DURABILITY
- + PRODUCTIVITY
- + FUEL EFFICIENCY
- + TECHNOLOGY
- + VERSATILITY

Experience higher performance while reducing costs and fuel consumption with Cat wheel loaders.



# SUPERIOR FUEL EFFICIENCY



---

## ADVANCED SYSTEMS WITH INNOVATIVE INTEGRATION

The deep system integration of the engine and emissions system, power train, hydraulic system, and cooling system lower engine speeds and overall system heat loads, resulting in significantly increased performance and fuel efficiency.

---

## SMART SPEED CONTROLS

Lowering the rated engine speed and eliminating the torque converter result in machine speed that can be controlled independently of the engine RPM. This also allows you to decelerate the machine using engine and hydraulic retarding, saving service brake wear.

---

## ENGINE AND EMISSIONS

High power density and fuel efficiency set our engines apart. Certified to meet emission standards, our engines feature Cat electronics, fuel injection, and air-management systems.

---

## EFFICIENT POWER TRAIN

Running the engine at lower RPM, optimizing the power flow through the transmission, combined with the dedicated hydraulic system significantly improves fuel efficiency with the highest performance capability.

### PROVEN FUEL SYSTEM

Cat injection timing regulates the fuel injection process through a series of timed microbursts, providing more control of combustion for the cleanest, most efficient fuel burn.

### AFTERTREATMENT TECHNOLOGIES

The Cat Clean Emissions Module delivers the performance and efficiency that customers demand, while meeting emission standards. It is completely automatic and does not interrupt the machine's work cycle.



---

## UP TO 25% LOWER MAINTENANCE COSTS\*

Save time and money with extended maintenance intervals and remote troubleshooting and flash capability. Get a better view of maintenance points with the optional underhood service light system.

---

## SMART MACHINE FOR EFFICIENT OPERATION

Integrated Cat technologies like Cat Payload with Assist make machine operation easier, so your jobsite is more productive. New Autodig offers partially and full automated loading for increased efficiency.

---

## UP TO 35% BETTER FUEL EFFICIENCY\*

Lower engine speeds result in reduced fuel burn. Continuously Variable Transmission with advanced rimpull control as well as integrated power train and hydraulic systems deliver superior performance and fuel efficiency.

## MAXIMIZE EFFICIENCY RIGHT FROM THE CAB

Cat wheel loaders feature integrated technologies that help make your operation more efficient.

### CAT PAYLOAD WITH ASSIST

- + Achieve precise load targets every time
- + Track daily production

### AUTODIG WITH AUTO SET TIRES

- + Boost productivity with automated loading
- + Reduce tire wear

### JOB AIDS

- + Make machine operation easier

A MORE EFFICIENT JOBSITE MEANS  
**MORE PROFIT IN EVERY LOAD.**

\*Compared to previous Cat models.

\*\*Not legal for trade.

# CAT CONTINUOUSLY VARIABLE TRANSMISSION

Our advanced transmission delivers smooth operation, fast acceleration, and high speed on grade.



## SIMPLE OPERATOR INTERFACE

Reduced operating complexity offers more comfort, better control, and less fatigue every shift.

## RIGHT PEDAL CONTROL – GO

The right hand pedal allows you to control machine speed and desired rimpull independently from engine RPM. It features a lock function to enhance operating comfort.

## LEFT PEDAL MODULATION – STOP

The left hand pedal provides integrated rimpull modulation and retarding functions. It will help reduce tire slip in the dig and brake wear using machine system to slow down the machine.

## EASY MANEUVERABILITY

Machine maneuvering is made easy with creep capability and hill-hold on grade.

## ADVANCED POWER DIAGNOSTIC

On-board diagnostic replaces stall testing and offers additional troubleshooting information.

## SIMPLIFIED TRANSMISSION CONTROL STRATEGY

- Programmable Virtual Gears
  - Allows the operator to remain in full machine control without impacting fuel efficiency.
- Fully Automatic
  - The continuously variable transmission does not require adequate gear selection from the operator and always delivers desired rimpull or speed.
- Integrated Flexibility
  - Separate virtual gears can be set for speed control, simplifying machine operation.
- Steady Deceleration
  - Modulate rimpull and speed with either pedal to engage pile with maximum efficiency.
- Simple Directional Shifting
  - Initiate directional changes at any speed and let the machine retard without applying the brakes or modulating throttle for smooth operation and increased operator comfort.





# PRODUCTIVE RESULTS

WORK SMART AND MOVE MORE

## ON-BOARD JOB AIDS

Job Aids help make machine operation easier, while also allowing your operators improve and optimize their skills on the jobsite.

## CONTINUOUS VARIABLE TRANSMISSION

No shift delays or engine underspeed situations affect the productivity of the machine.

## OPTIMIZED RIDE CONTROL SYSTEM

Dual accumulator system enables a better ride in loaded and unloaded situations. It improves smoothness over rough terrain, increasing confidence and efficiency and ensuring excellent material retention.

## PERFORMANCE SERIES BUCKETS

Easy-to-load Performance Series Buckets improve material retention and reduce dig times, significantly improving productivity and fuel efficiency, resulting in unsurpassed production capabilities with increased fill factors – ranging from 100% to 115%.

## BETTER TRACTION

New Autodig with Auto Set Tires assures that the front tires have adequate traction for consistent high bucket fill factors delivering up to 10% more productivity compared to previous models. Front manual differential lock is standard with optional automatic front and rear locks.

## AGGREGATE HANDLER

Aggregate packages are specialized offerings for loose aggregate rehandling applications. Payloads can be increased above other applications by installing larger buckets and counterweights in compliance with Caterpillar payload policy.

## THE RIGHT MIX OF FEATURES

Fine-tuned for the right applications:

- + BETTER FUEL ECONOMY, MAXIMIZED UPTIME, AND LOWER MAINTENANCE COSTS
- + HIGH POWER AND PERFORMANCE ACROSS A VARIETY OF APPLICATIONS
- + ENHANCED RELIABILITY THROUGH COMMONALITY AND SIMPLICITY OF DESIGN
- + WORLD-CLASS SUPPORT FROM THE CAT DEALER NETWORK
- + DURABLE DESIGNS WITH LONG LIFE TO OVERHAUL



## ADVANCED POWER TRAIN

Power is transmitted through a continuous variable parallel path transmission. Combining direct mechanical and Hystat power paths maximizes efficiency over a wide range of operating conditions.



## DURABLE AXLES

Axles are designed to handle your most extreme applications. The rear axle oscillates to  $\pm 13$  degrees for excellent stability and traction on even the roughest terrain.



## QUICK COUPLERS AND WORK TOOLS

For versatility, buckets and components can be changed without leaving the cab, allowing the machine to quickly move from task to task.



## OPTIMIZED HYDRAULICS

Our hydraulic systems come equipped with a monoblock main hydraulic valve. This design reduces weight while decreasing leak points by 40%.



## DURABLE FRAMES

The robotically welded two-piece structural frame absorbs impact associated with excavation and loading, while the hitch system provides high bearing force capacity.



## EXTENSIVE RANGE OF ATTACHMENTS

Do more jobs with one machine. An extensive range of work tools and bucket styles are available to optimize these machines for your operation.





# SMART MACHINE FOR EFFICIENT OPERATION

## INNOVATIVE CAT TECHNOLOGIES



Your machine comes equipped with innovative Cat technologies that give you the edge. Operators of all experience levels will dig and load with more confidence, speed, and accuracy. The result? Better productivity and lower costs.



### CAT PAYLOAD\* WITH ASSIST

Cat Payload technology delivers precise bucket load information with on-the-go weighing, which helps prevent over- or underloading. The low lift weigh and manual tip-off functions optimize the final bucket process and maximize efficiency.



### CAT ADVANCED PAYLOAD\* WITH ASSIST

The optional advanced system adds features like list management. It also includes tip-off-assist, which automatizes the final bucket load adjust process. With multi-task mode, the operator can track two loading processes. The advanced platform is also ready for Dispatch for Loading, integrating the loader into the scale house process (requires compatible third-party scale house software and subscription).



### DETECT

Rearview camera is standard. This system can be enhanced with an additional display dedicated to the rearview camera as well as for a Multiview (360 degree) system. To complete the Cat Detect offerings, the machines can be equipped with a rear radar system, which features speed-sensitive alerts and ground clutter filtering to avoid annoyance.



### CAT PRODUCTIVITY

A Cat Productivity subscription provides comprehensive, actionable information to help you manage and improve the productivity and profitability of your operations.

\*Not legal for trade.



# REAL-TIME INFORMATION FROM CAT EQUIPMENT MANAGEMENT TAKES THE GUESSWORK OUT OF MANAGING YOUR EQUIPMENT

Cat Equipment Management technologies work together to put equipment information at your fingertips. Get real-time access to information on every machine in your fleet on any jobsite – no matter the size of the operation or the brands of equipment you run.



## **PRODUCT LINK™**

Product Link collects data automatically and accurately from your assets. Information such as location, hours, fuel usage, idle time, maintenance alerts, diagnostic codes, and machine health can be viewed online through web and mobile applications.



## **VISIONLINK®**

Access information anytime, anywhere with VisionLink and use it to make informed decisions that boost productivity, lower costs, simplify maintenance, and improve safety and security on your jobsite. With different subscription level options, your Cat dealer can help you configure exactly what you need to connect your fleet and manage your business without paying for extras you don't want. Subscriptions are available with cellular or satellite reporting (or both).



## **REMOTE SERVICES**

The Cat App helps you manage your assets – at any time – right from your smartphone. See fleet location and hours, get critical required maintenance alerts, and even request service from your local Cat dealer.

- + **Remote Troubleshoot** can connect the machine to the dealer service department to help diagnose problems quickly so you can get back to work.
- + **Remote Flash** – get software updates sent to your machine remotely.
- + **Operator ID** lets you track machine operation by individual operator using the main display and Product Link.

# WORK IN COMFORT

## IN THE ALL-NEW CAB

The cab is designed to maximize comfort and productivity, offering a quieter, more spacious operating environment and intuitive controls to help reduce the fatigue, stresses, sounds, and temperatures of a demanding job.



### CAB ACCESS

Inclined steps, large opening door, optional remote door opener, and convenient grab handles ease accessibility to the operating space.



### OPERATOR ID

Secure machine usage with dedicated Operator IDs. Machine settings are saved separately, increasing shift change efficiency. Unlock the machine using Passcode or optional Bluetooth® key.



### GREATER VISIBILITY

Extended windows enhance visibility while convex and spot mirrors extend the driver's view on the sides and rear.



### ADVANCED SEAT & MORE LEGROOM

The next generation of operator comfort includes increased legroom and an easily adjustable seat with updated styling and an enhanced suspension system. It comes in three trim levels and can be equipped with a dealer-installed 4-point harness.



### NOISE REDUCTION

Sound-suppression, seals, and viscous cab mounts decrease noise for a quieter work environment.



### JOYSTICK STEERING

The seat-mounted electro-hydraulic joystick steering system provides precision control and dramatically reduces arm fatigue, resulting in excellent comfort and accuracy.



# SIMPLE CONTROLS AT YOUR FINGERTIPS

---

## TOUCHSCREEN DISPLAY

The easy and intuitive interface lets the operator work with confidence and efficiency. It includes Operator ID, machine settings, Job Aids, help functions, security, rear-vision camera, and integrated Cat Payload with Assist.



---

## CENTRAL DISPLAY

Featuring easy-to-read analog gauges and LED indicators that allow the operator to quickly monitor critical machine health parameters.

A large text box displays the Cat Payload information as well as gear selection, machine travel speed, time, and hour meter.



---

## KEYPADS

Easy-to-reach backlit keypads on the implement control pod and the A-post provide instant access to many functions and settings. Only active buttons or functions are illuminated, making it very intuitive for the operator.





REDUCED MAINTENANCE TIME AND COSTS BY  
**UP TO 25%\***

Cat wheel loaders are easy to maintain and service, eliminating any potential waste of time or money. Major components are rebuildable, giving the machine a second life, and often a third life.

**KEY FEATURES SAVING YOU TIME, MONEY, AND ENERGY:**

- + Convenient access to hydraulic and electrical service centers for easy and safe servicing.
- + Remote Troubleshoot can connect the machine to the dealer service department to help diagnose problems quickly so you can get back to work.
- + Remote Flash works around your schedule to ensure your machine's software is up to date for optimal performance.
- + Integrated Autolube extends component and service life.
- + One-piece tilting hood makes engine compartment access fast and easy.

**THE CAT® 972 XE SAVES TIME AND MONEY WITH EASIER AND FASTER SERVICE**



**REBUILDABLE COMPONENTS**



**EASY ACCESS TO SERVICE CENTERS**



**REMOTE TECHNOLOGIES**  
MANAGE YOUR MACHINE FROM ANYWHERE

\*Parts and fluids only



# DO MORE JOBS

## VERSATILE ATTACHMENTS AND COUPLERS

For worksites that demand more, you need a wheel loader that is purpose-built for the job. Cat work tools are engineered to handle all of your specific application needs.



### STANDARD Z-BAR LINKAGE

The proven Z-bar linkage combines digging efficiency with sharp visibility, resulting in excellent excavation, high breakout forces, and superior production capabilities.

### QUICK COUPLERS AND WORK TOOL ATTACHMENTS

A wheel loader equipped with a Cat Fusion™ quick coupler system is a much more versatile machine. Buckets and work tools can be changed without leaving the cab – allowing the machine to quickly move from task to task. Consult your local dealer for availability of a variety of specialty buckets and forks.

### PERFORMANCE SERIES BUCKETS

Performance Series Buckets use a system-based approach to balance bucket shape with the machine's lift and tilt capacity, weight, and linkage. A variety of work tools and bucket styles are available for a range of applications, including general purpose, flat floor, heavy duty rock, and coal-style buckets.

- + Easy loading
- + Fuel efficient
- + Carry more
- + Lower operating costs
- + Higher productivity

### HIGH LIFT LINKAGE

The optional high lift linkage offers increased hinge pin height to load more easily in a variety of applications with any type of bucket or fork.

### PURPOSE-BUILT SPECIALTY CONFIGURATIONS

Maximize your wheel loader's performance and durability in the toughest applications with application-specific arrangements direct from the factory.

**Industrial and waste models** – guarding and reinforcement protect components when working in transfer stations, recycling depots, scrap yards, and demolition sites.

# TECHNICAL SPECIFICATIONS

See [cat.com](http://cat.com) for complete specifications.

ENGINE			
Engine Model	Cat® C9.3B		
Engine Power @ 1,600 rpm – ISO 14396:2002	253 kW	339 hp	
Gross Power @ 1,600 rpm – SAE J1995:2014	256 kW	343 hp	
Net Power @ 1,600 rpm – ISO 9249:2007, SAE J1349:2011	236 kW	316 hp	
Engine Torque @ 1,200 rpm – ISO 14396:2002	1864 N·m	1,375 lbf·ft	
Gross Torque @ 1,200 rpm – SAE J1995:2014	1882 N·m	1,388 lbf·ft	
Net Torque @ 1,200 rpm – ISO 9249:2007, SAE J1349:2011	1745 N·m	1,287 lbf·ft	
Displacement	9.3 L		

- Cat engine meets U.S. EPA Tier 4 Final and EU Stage V emission standards.
  - The net power advertised is the power available at the flywheel when the engine is equipped with fan, alternator, air cleaner, and aftertreatment.
  - Cat engines are compatible with the following renewable, alternative, and bio-fuels\* with lower greenhouse gas emission impact:
    - Up to B20 biodiesel (FAME) \*\*
    - Up to 100% HVO and GTL renewable fuels
- \* Refer to guidelines for successful application. Please consult your Cat dealer or "Caterpillar Machine Fluids Recommendations" (SEBU6250) for details.  
 \*\* For use of higher blends, consult your Cat dealer.

WEIGHT		
Operating Weight	24 890 kg	54,858 lb

- Weight based on a machine configuration with Bridgestone 26.5R25 VJT L3 radial tires, full fluids, operator, standard counterweight, ride control, cold start, roading fenders, Product Link, front manual differential/open rear axles, power train guard, secondary steering, sound suppression, and a 4.8 m<sup>3</sup> (6.25 yd<sup>3</sup>) general purpose bucket with BOCE.

BUCKET CAPACITIES			
Bucket Range	2.8- 14.0 m <sup>3</sup>	3.75- 18.25 yd <sup>3</sup>	

TRANSMISSION					
Forward 1	6.9 km/h	4.3 mph	Reverse 1	6.9 km/h	4.3 mph
Forward 2	12.9 km/h	8.0 mph	Reverse 2	12.9 km/h	8.0 mph
Forward 3	22.7 km/h	14.1 mph	Reverse 3	28.7 km/h	17.9 mph
Forward 4	39.5 km/h	24.5 mph	Reverse 4	N/A	N/A

- Maximum travel speed in standard vehicle with empty bucket and standard L3 tires with 849 mm (33 in) roll radius.

SOUND		
With Cooling Fan Speed at Maximum Value:		
Operator Sound Pressure Level (ISO 6396:2008)	67 dB(A)	
Exterior Sound Power Level (ISO 6395:2008)	107 dB(A)	
Exterior Sound Pressure Level (SAE J88:2013)	74 dB(A)*	

\*Distance of 15 m (49.2 ft), moving forward in second gear ratio.

With Cooling Fan Speed at 70% of Maximum Value:**		
Operator Sound Pressure Level (ISO 6396:2008)	67 dB(A)	
Exterior Sound Power Level	105 dB(A)***	

\*\*For machines in European Union countries and in countries that adopt the "EU Directives."

\*\*\*European Union Directive "2000/14/EC" as amended by "2005/88/EC."

OPERATING SPECIFICATIONS			
Static Tipping Load – Full 37° Turn – with Tire Deflection	16 297 kg	35,919 lb	
Static Tipping Load – Full 37° Turn – No Tire Deflection	17 505 kg	38,582 lb	
Breakout Force	196 kN	44,702 lbf	

- For a machine configuration as defined under "Weight."
- Full compliance to ISO 14397-1:2007 Sections 1 thru 6, which requires 2% verification between calculations and testing.

SERVICE REFILL CAPACITIES		
Fuel Tank	303 L	80.1 gal
DEF Tank	26 L	6.9 gal
Cooling System	66 L	17.4 gal
Crankcase	23 L	6.1 gal
Transmission	63 L	16.6 gal
Differentials and Final Drives – Front	57 L	15.1 gal
Differentials and Final Drives – Rear	57 L	15.1 gal
Hydraulic Tank	114 L	30.1 gal

HYDRAULIC SYSTEM		
Implement System:		
Maximum Pump Output (1,400 rpm)	348 L/min	92 gal/min
Maximum Operating Pressure	31 000 kPa	4,496 psi
Hydraulic Cycle Time – Total	10.1 seconds	

DIMENSIONS				
	Standard Lift		High Lift	
Height to Top of Hood	2846 mm	9'4"	2846 mm	9'4"
Height to Top of Exhaust Pipe	3527 mm	11'7"	3527 mm	11'7"
Height to Top of ROPS	3589 mm	11'10"	3589 mm	11'10"
Ground Clearance	420 mm	1'4"	420 mm	1'4"
Center Line of Rear Axle to Edge of Counterweight	2458 mm	8'0"	2458 mm	8'0"
Center Line of Rear Axle to Hitch	1775 mm	5'10"	1775 mm	5'10"
Wheelbase	3550 mm	11'8"	3550 mm	11'8"
Overall Length (without bucket)	7731 mm	25'5"	8069 mm	26'6"
Hinge Pin Height at Maximum Lift	4464 mm	14'7"	4800 mm	15'8"
Hinge Pin Height at Carry	682 mm	2'2"	780 mm	2'6"
Lift Arm Clearance at Maximum Lift	3842 mm	12'7"	4179 mm	13'8"
Rack Back at Maximum Lift	56 degrees		71 degrees	
Rack Back at Carry Height	49 degrees		49 degrees	
Rack Back at Ground	39 degrees		37 degrees	
Width over Tires (Loaded)	3011 mm	9'11"	3011 mm	9'11"
Tread Width	2230 mm	7'3"	2230 mm	7'3"

- All dimensions are approximate and based on machine equipped with 4.8 m<sup>3</sup> (6.25 yd<sup>3</sup>) general purpose bucket with BOCE and Bridgestone 26.5R25 VJT L3 radial tires.

AIR CONDITIONING SYSTEM	
The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 1.6 kg (3.5 lb) of refrigerant which has a CO <sub>2</sub> equivalent 2.288 metric tonnes (2.522 tons).	



# STANDARD & OPTIONAL EQUIPMENT

Standard and optional equipment may vary. Consult your Cat dealer for details.

OPERATOR ENVIRONMENT	STANDARD	OPTIONAL
Cab, pressurized, sound suppression	●	
Door, remote opening system	●	
EH implement controls, parking brake	●	
Steering, joystick	●	
Entertainment radio (FM, AM, USB, BT)		●
Entertainment radio (DAB+)		●
CB radio ready		●
Seat, suede/cloth, air suspension, heated	●	
Seat, leather/cloth, air suspension, heated/cooled		●
4-point seat belt (kit)		●
Touchscreen display	●	
Visibility: mirrors, rear-vision camera	●	
Multiview (360°) vision system		●
Cat Detect rear radar system		●
Dedicated rearview screen		●
Mirrors, heated	●	
Air conditioner, heater, defroster (auto temp, fan)	●	
Sun visor, front, retractable	●	
Sun visor, rear, retractable	●	
Window cleaning platform, front	●	
Window, front, laminated	●	
Windows, front, heavy duty		●
Full cab window guard		●
ON-BOARD TECHNOLOGIES	STANDARD	OPTIONAL
Cat Payload scale	●	
Autodig with Auto Set Tires	●	
Operator ID & machine security	●	
Application Profiles	●	
Job Aids	●	
Controls Help and eOMM	●	
Cat Advanced Payload		●
Cat Payload Printer		●
POWER TRAIN	STANDARD	OPTIONAL
Cat C9.3B engine	●	
Electric fuel priming pump	●	
Fuel-water separator and secondary fuel filter	●	
Engine, air precleaner	●	
Turbine, air precleaner		●
Radiator, high debris		●
Cooling fan, reversible		●
Axles, front differential lock	●	
Axles, auto differential locks front and rear		●
Axles, ecology drains	●	
Axles, AOC ready, extreme temperature seals		●
Axles, oil cooler		●
Transmission, continuous variable	●	
Rimpull control	●	
Throttle lock mode	●	
Hill and speed hold on grades	●	

POWER TRAIN (CONTINUED)	STANDARD	OPTIONAL
Service brakes, hydraulic, fully enclosed wet disc, wear indicators	●	
Park brake, caliper on front axles, spring applied–pressure released	●	
HYDRAULICS	STANDARD	OPTIONAL
Implement system, load sensing with electro-hydraulic variable displacement piston pump	●	
Steering system, load sensing with dedicated variable displacement piston pump	●	
Ride control, dual accumulators	●	
3 <sup>rd</sup> and 4 <sup>th</sup> auxiliary functions with ride control		●
Oil sampling valves, Cat XT™ hoses	●	
Quick coupler control		●
ELECTRICAL	STANDARD	OPTIONAL
Starting and charging system, 24V	●	
Starter, electric, heavy duty	●	
Cold start, 120V or 240V		●
Lights: halogen, 4 work lights, 2 rear-vision work lights	●	
Lights: roading with turn signals	●	
Lights: LED		●
Warning beacon		●
MONITORING SYSTEM	STANDARD	OPTIONAL
Front dash with analog gauges, LCD display, and warning lights	●	
Primary touchscreen monitor (Cat Payload, quad screens, machine settings & messages)	●	
Reversing strobe lights		●
LINKAGE	STANDARD	OPTIONAL
Standard lift, Z-bar	●	
High lift, Z-bar		●
Kickouts: lift and tilt	●	
ADDITIONAL EQUIPMENT	STANDARD	OPTIONAL
Cat Autolube system		●
Fenders, roading		●
Guards: power train, crankcase, cab, cylinders, rear		●
Biodegradable hydraulic oil		●
High-speed oil change system		●
Toolbox		●
Wheel chocks		●
Secondary steering system, electrical*		●
SPECIAL CONFIGURATIONS	STANDARD	OPTIONAL
Aggregate handler		●
Waste and industrial		●
Corrosion resistant		●

\*Standard where mandated

For more complete information on Cat products, dealer services and industry solutions, visit us on the web at [www.cat.com](http://www.cat.com)

VisionLink® is a trademark of VirtualSite Solutions LLC, registered in the United States and in other countries.

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

© 2021 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, Fusion, XT, Product Link, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

[www.cat.com](http://www.cat.com) [www.caterpillar.com](http://www.caterpillar.com)

AEXQ3313-00  
Build Number: 14A  
(N Am, Europe, Aus-NZ)

